

File E96454
Project 4788448217

July 31, 2018

REPORT

On

ATTACHMENT PLUGS, FUSELESS

SCHURTER AG
LUZERN, CH-6002, SWITZERLAND

Copyright © 2018 UL LLC

UL LLC authorizes the above named company to reproduce this Report only for purposes as described in the Conclusion. The Report should be reproduced in its entirety; however to protect confidential product information, the Construction Details Descriptive pages may be excluded.

DESCRIPTION

PRODUCT COVERED:

USL, CNL - Appliance Connector, Series 4781, 4782, 4784 and 4785. Refer to Nomenclature Breakdown for type designations.

GENERAL:

These 2-pole, 3-wire Appliance Connectors are rated 15 A, 250 V ac. The subject devices have been investigated to UL 60320-1, cold or hot condition. This device configuration and voltage rating are as indicated below:

Cat No./ Series	Electrical Rating	Configuration
4781 4784	15 A, 250 V ac	C15
4782 4785	15 A, 250 V ac	C13

USL - Indicates investigation to the requirements of the Standard for Appliance Couplers For Household And Similar General Purposes, UL 60320-1,.

CNL - Indicates investigation to the requirements of the Canadian National Standards for Appliance Couplers For Household And Similar General Purposes, C22.2 No. 60320-1.

NOMENCLATURE BREAKDOWN

Series 4781 and 4782

XXXX - 0 X X 0 - 0 0
I II III

I - Series

4781 = Series 4781 (C15, straight)

4782 = Series 4782 (C13, straight)

*

II - Cable Guard

0 = for cable max. diameter 8.5 mm

1 = for cable max. diameter 10 mm

*III - Color

0 = black

1 = **grey**2 = **white****Series 4784 and 4785**

XXXX - 0 X X 0 - 0 0
I II III

I - Series

4784 = Series 4784 (C15, angled)

4785 = Series 4785 (C13, angled)

II - Cable Guard

0 = for cable max. diameter 8.5 mm

1 = for cable max. diameter 10 mm

III - Color

0 = black