

## DESCRIPTION

## PRODUCT COVERED:

USR, CNR : Appliance Outlet with overload protection, Series 4719 with Fuse Carrier FC11. Refer to Nomenclature Breakdown for type designations.

## GENERAL:

These devices are with 2-pole, 3-wire configuration. This device configuration and voltage rating are as indicated below:

Series	Electrical Rating Fuse holder	Electrical [Configuration] Rating Appliance Outlet	Configuration Appliance Outlet
4719 (with FC11)	10 A, 250 V ac	15 A, 250 V ac	F

May be provided with additional suffixes consisting of up to three digits which are provided for commercial purposes or packaging variations.

USR - Indicates investigation to the requirements of the Standard for Appliance Couplers For Household And Similar General Purposes, UL 60320-1

CNR - Indicates investigation to the requirements of the Canadian National Standards for Appliance Couplers For Household And Similar General Purposes, C22.2 No. 60320-1-11.

## ENGINEERING CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Use - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

1. The suitability of the mounting means shall be determined in the end use.
2. The suitability at electrical connection to the terminal shall be determined in the end use application.
3. The suitability of single fuse operation shall be determined in the end use application.
4. These devices shall be installed in compliance with the enclosure, mounting, spacing, casualty, and segregation requirements in each end-use application.
5. The maximum temperature rise on terminal of the component shall not exceed 45°C during end-use application
6. Appliance inlets for cold conditions are not intended to be used with heating appliances having external metal parts.

## NOMENCLATURE BREAKDOWN SERIES 4719

4719 - X X X X - X X 0 0  
I II III IV V VI

## I - Terminal L

- 1 = Connection
- 2 = Connection with Solder Terminal

## II - Terminal N

- 0 = Quick Connect 6.3 x 0.8 mm
- 1 = Quick Connect 4.8 x 0.8 mm
- 2 = Solder

## III - Terminal PE

- 0 = Quick Connect 6.3 x 0.8 mm
- 1 = Quick Connect 4.8 x 0.8 mm
- 2 = Solder

## IV - Terminal Fuse holder

- 0 = Quick Connect 6.3 x 0.8 mm
- 1 = Quick Connect 4.8 x 0.8 mm
- 2 = Solder

## V - Mounting

- 3 = Snap-in 1.0 mm
- 4 = Snap-in 1.5 mm
- 5 = Snap-in 2.0 mm
- 6 = Snap-in 2.5 mm
- 7 = Snap-in 3.0 mm
- 8 = Snap-in 1.2 mm

## VI - Neon

- 0 = without
- 1 = with

## NOMENCLATURE BREAKDOWN Fuse Carrier FC11

FC11 - 0 0 X X  
I II

## I - Sealing Version

- 0 = without O-ring
- 1 = with O-ring

## II - Color

- 0 = black
- 1 = white