

DESCRIPTION

PRODUCT COVERED:

USL, CNL Attachment Plug, Series 9009, 4789 and 4796.

GENERAL:

All plugs are 2 pole, 3-wire grounding devices.

Series 9009 is rated 15 A, 250 Vac.

Series 4789 and 4796 are rated 20 A, 250 Vac.

USL - Indicates investigation to the requirements of the Standard for Appliance Couplers For Household And Similar General Purposes, UL 60320-1, Edition 2.

CNL - Indicates investigation to the requirements of the Standard for Appliance Couplers For Household And Similar General Purposes, C22.2 No. 60320-1-11, First Edition.

Nomenclature Breakdown

MODEL NOMENCLATURE 9009:

9009 - $\frac{X}{I}$ $\frac{X}{II}$ $\frac{X}{III}$ $\frac{X}{IV}$ - $\frac{XX}{VI}$

I = Model designation
9009 = Straight model

II = Locking System
0 = without V-Lock
1 = with V-Lock
2

III = Cable Guard
1 = for cable max. Ø 8(10)mm
2 = for cable max. Ø 10mm

IV = Color
1 = black
2 = grey

V = Delivery form
1 = assembled
2 = disassembled

VI = Customer Specific Type
00 = Standard

MODEL NOMENCLATURE 4789:

$\frac{4789}{I}$ - 1 $\frac{X}{II}$ 0 0

I = Model designation
4789 = Angled model

II = Cable Guard
1 = for cable max. Ø 8(10)mm
2 = for cable max. Ø 10mm

MODEL NOMENCLATURE 4796:

$\frac{4796}{I}$ - 0 $\frac{X}{II}$ 0 0

I = Model designation
4796 = Straight model

II = Cable Guard
0 = for cable max. Ø 8(10)mm
1 = for cable max. Ø 10mm