File E96454	Vol. 2	Sec. 10	Page 1	Issued:	2014-09-26
		and Report		Revised:	2015-09-25

DESCRIPTION

PRODUCT COVERED:

*USL, CNL - Cord Connector, Series 0101. Refer to Nomenclature Breakdown for type designations.

*USL, CNL - Cord Connector, Series. 4771 and 4772. Refer to Nomenclature Breakdown for type designations.

GENERAL:

These 2-pole, 3-wire Cord Connectors are rated 15 A, 250 V ac. The subject devices have been investigated to UL 60320-1 Class (I) equipment, hot or very hot condition. This device configuration and voltage rating are as indicated below:

Cat No./ Series	Electrical Rating	Configuration	
0101	15 A, 250 V ac	C15	
4771	15 A, 250 V ac	C15A	
4772	15 A, 250 V ac	C15A	

USL - Indicates investigation to the requirements of the Standard for Appliance Couplers For Household And Similar General Purposes, UL 60320-1, Edition 2.

CNL - Indicates investigation to the requirements of the Canadian National Standards for Appliance Couplers For Household And Similar General Purposes, C22.2 No. 60320-1, First Edition.

File E96454	Vol. 2	Sec. 10	Page 2	Issued:	2014-09-26
		and Report		Revised:	2017-01-24

NOMENCLATURE BREAKDOWN

*

XXXX - X X 10-00 I II Ι Ι = Product Type 0101 = straight cord connector for hot conditions 4771 = straight cord connector for very hot conditions 4772 = angled cord connector for very hot conditions II = Contacts 0 = standard 1 = gold plated III = Cable Guard = for max. cable diameter 8(10) mm 1 2 = for max. cable diameter 10 mm

Created by UL Document Assembler 2017-01-30 09:40:50 -06:00