

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

**Issued to:** SCHURTER AG  
Werkhofstrasse 8-12  
P.O.Box  
CH-6002 Lucerne SWITZERLAND

**This certificate confirms that representative samples of** COMPONENT - RECEPTACLES FOR PLUGS AND ATTACHMENT PLUGS

Refer addendum page for models

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**Standard(s) for Safety:** UL 60320-1 & CSA C22.2 No.60320-1-11, Appliances Couplers for Household and Similar General Purposes

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USR/CNR Component Appliance Outlet, Series 4710, 4710-5, 4797 and 4797-5. Refer to Nomenclature Breakdown for type

## NOMENCLATURE BREAKDOWN SERIES 4710

4710	-	0	X	X	X	-	0	0	0	0	-	X	XX	-	X	1	00
			I	II	III							IV	V		VI		

### I – Terminal L

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG
- 4 = Solder Terminal
- 6 = Quick-connect 6.3 x 0.8 mm

### II – Terminal N

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

### III – Terminal PE

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

### IV – Arrangement

- 1 = along
- 2 = cross

### V – Panel mounting

- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.2 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm

### VI – Color

- 1 = black
- 2 = grey
- 3 = white



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

## NOMENCLATURE BREAKDOWN SERIES 4710-5

4710-5		X	X	X	-	X	X	X	X	-	X	XX	-	X	X	00
		I	II	III		IV	V	VI	VII		VIII	IX		X	XI	

### I – Terminal L

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG
- 4 = Solder Terminal
- 6 = Quick-connect 6.3 x 0.8 mm
- 7 = PCB terminal 2.8 x 0.8 mm

### II – Terminal N

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

### III – Terminal PE

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

- IV – Light pipe position A      0=      without hole for light pipe
- 1 =      with hole for light pipe

- V – Light pipe position B  
Same numbers as “IV – Light pipe position A”

- VI – Light pipe position C  
Same numbers as “IV – Light pipe position A”

- VII – Light pipe position D  
Same numbers as “IV – Light pipe position A”

### VIII – Arrangement

- 1 = along
- 2 = cross

### IX – Panel mounting

- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.5 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>





# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

X – Color  
 1 = black  
 2 = grey  
 3 = white

XI – Glow wire requirements (IEC)  
 0 = GWIT standard  
 1 = GWIT enhanced

## NOMENCLATURE BREAKDOWN SERIES 4797

4797	-	0	X	X	X	-	0	0	0	0	-	XX	X	-	00
			I	II	III							IV	V		

### I – Terminal L

1 = Solder terminal  
 2 = Quick-connect 6.3 x 0.8 mm

### II – Terminal N

1 = Solder terminal  
 2 = Quick-connect 6.3 x 0.8 mm

### III – Terminal PE

0 = without terminal (PC II)  
 1 = Solder terminal  
 2 = Quick-connect 6.3 x 0.8 mm

### IV – Panel mounting

00 = screw mounting  
 10 = snap-in 1.0 mm  
 12 = snap-in 1.2 mm  
 15 = snap-in 1.5 mm  
 20 = snap-in 2.0 mm  
 25 = snap-in 2.5 mm  
 30 = snap-in 3.0 mm

### V – Color

1 = black  
 2 = grey  
 3 = white



Bruce Mahrenholz, Director North American Certification Program  
 UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

**NOMENCLATURE BREAKDOWN SERIES 4797-5**

4797-5		X	X	X	-	X	X	X	X	-	X	XX	X	-	00
		I	II	III		IV	V	VI	VII		VIII	IX	X		

I – Terminal L  
4 = PCB terminal 2.8 x 0.8 mm

II – Terminal N  
4 = PCB terminal 2.8 x 0.8 mm

III – Terminal PE  
4 = PCB terminal 2.8 x 0.8 mm

IV – Light pipe position A  
 0 = without hole for light pipe  
 1 = with hole for light pipe  
 3 = Light pipe, L = 27.5 mm  
 4 = Light pipe, L = 32.7 mm  
 5 = Light pipe, L = 37.4 mm  
 6 = Light pipe, L = 50.0 mm

V – Light pipe position B  
Same numbers as “IV – Light pipe position A”

VI – Light pipe position C  
Same numbers as “IV – Light pipe position A”

VII – Light pipe position D  
Same numbers as “IV – Light pipe position A”

IX – Panel mounting  
 10 = snap-in 1.0 mm  
 12 = snap-in 1.2 mm  
 15 = snap-in 1.5 mm  
 17 = snap-in 1.7 mm  
 20 = snap-in 2.0 mm  
 25 = snap-in 2.5 mm  
 30 = snap-in 3.0 mm

X – Color  
 1 = black  
 2 = grey  
 3 = white



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

