

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

**Issued to:** SCHURTER AG  
Werkhofstrasse 8-12  
P.O.Box  
CH-6002 Lucerne SWITZERLAND

**This certificate confirms that  
representative samples of**

COMPONENT - RECEPTACLES FOR PLUGS AND  
ATTACHMENT PLUGS

Refer addendum page for models

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**Standard(s) for Safety:**

UL 60320-1 & CSA C22.2 No.60320-1-11, Appliances Couplers for Household and Similar General Purposes

**Additional Information:**

See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USR/CNR Component Appliance Outlet, Series 4710, 4710-5, 4797 and 4797-5. Refer to Nomenclature Breakdown for type

## NOMENCLATURE BREAKDOWN SERIES 4710

4710	-	0	X	X	X	-	0	0	0	0	-	X	XX	-	X	1	00
			I	II	III							IV	V		VI		

### I – Terminal L

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG
- 4 = Solder Terminal
- 6 = Quick-connect 6.3 x 0.8 mm

### II – Terminal N

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

### III – Terminal PE

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

### IV – Arrangement

- 1 = along
- 2 = cross

### V – Panel mounting

- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.2 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm

### VI – Color

- 1 = black
- 2 = grey
- 3 = white

*B. Mahlenz*

Bruce Mahlenz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

## NOMENCLATURE BREAKDOWN SERIES 4710-5

4710-5		X	X	X	-	X	X	X	X	-	X	XX	-	X	X	00
		I	II	III		IV	V	VI	VII		VIII	IX		X	XI	

### I – Terminal L

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG
- 4 = Solder Terminal
- 6 = Quick-connect 6.3 x 0.8 mm
- 7 = PCB terminal 2.8 x 0.8 mm

### II – Terminal N

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

### III – Terminal PE

- 1 = IEC-Contact 10 AWG
- 2 = IEC-Contact 12 AWG

- IV – Light pipe position A 0= without hole for light pipe  
 1 = with hole for light pipe

- V – Light pipe position B  
 Same numbers as “IV – Light pipe position A”

- VI – Light pipe position C  
 Same numbers as “IV – Light pipe position A”

- VII – Light pipe position D  
 Same numbers as “IV – Light pipe position A”

### VIII – Arrangement

- 1 = along
- 2 = cross

### IX – Panel mounting

- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.5 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm

*B. Mahlenz*

Bruce Mahlenz, Director North American Certification Program  
 UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

X – Color  
1 = black  
2 = grey  
3 = white

XI – Glow wire requirements (IEC)  
0 = GWIT standard  
1 = GWIT enhanced

## NOMENCLATURE BREAKDOWN SERIES 4797

4797	-	0	X	X	X	-	0	0	0	0	-	XX	X	-	00
			I	II	III							IV	V		

I – Terminal L  
1 = Solder terminal  
2 = Quick-connect 6.3 x 0.8 mm

II – Terminal N  
1 = Solder terminal  
2 = Quick-connect 6.3 x 0.8 mm

III – Terminal PE  
0 = without terminal (PC II)  
1 = Solder terminal  
2 = Quick-connect 6.3 x 0.8 mm

IV – Panel mounting  
00 = screw mounting  
10 = snap-in 1.0 mm  
12 = snap-in 1.2 mm  
15 = snap-in 1.5 mm  
20 = snap-in 2.0 mm  
25 = snap-in 2.5 mm  
30 = snap-in 3.0 mm

V – Color  
1 = black  
2 = grey  
3 = white

*B. Mahlenz*

Bruce Mahlenz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190605-E103791  
**Report Reference** E103791-20150804  
**Issue Date** 2019-JUNE-05

## NOMENCLATURE BREAKDOWN SERIES 4797-5

4797-5		X	X	X	-	X	X	X	X	-	X	XX	X	-	00
		I	II	III		IV	V	VI	VII		VIII	IX	X		

I – Terminal L  
 4 = PCB terminal 2.8 x 0.8 mm

II – Terminal N  
 4 = PCB terminal 2.8 x 0.8 mm

III – Terminal PE  
 4 = PCB terminal 2.8 x 0.8 mm

IV – Light pipe position A  
 0 = without hole for light pipe  
 1 = with hole for light pipe  
 3 = Light pipe, L = 27.5 mm  
 4 = Light pipe, L = 32.7 mm  
 5 = Light pipe, L = 37.4 mm  
 6 = Light pipe, L = 50.0 mm

V – Light pipe position B  
 Same numbers as “IV – Light pipe position A”

VI – Light pipe position C  
 Same numbers as “IV – Light pipe position A”

VII – Light pipe position D  
 Same numbers as “IV – Light pipe position A”

IX – Panel mounting  
 10 = snap-in 1.0 mm  
 12 = snap-in 1.2 mm  
 15 = snap-in 1.5 mm  
 17 = snap-in 1.7 mm  
 20 = snap-in 2.0 mm  
 25 = snap-in 2.5 mm  
 30 = snap-in 3.0 mm

X – Color  
 1 = black  
 2 = grey  
 3 = white

*B. Mahlenz*

Bruce Mahlenz, Director North American Certification Program  
 UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



File E103791  
Project 4786833933

Issued: August 4, 2015

REPORT

on

COMPONENT - RECEPTACLES FOR ATTACHMENT PLUGS AND PLUGS  
SCHURTER, AG  
Luzern, Switzerland

Copyright © 2015 UL LLC

UL LLC authorizes the above named company to reproduce this Report only for purposes as described in the Conclusion. The Report should be reproduced in its entirety; however to protect confidential product information, the Construction Details Descriptive pages may be excluded.

## D E S C R I P T I O N

## PRODUCT COVERED:

USR/CNR Component Appliance Outlet, Series 4710, 4710-5, 4797 and 4797-5. Refer to Nomenclature Breakdown for type

## GENERAL:

\*These devices are either 2 pole, 3 wire or 2 pole 2 wire Appliance Outlets provided with mounting flanges or snap mount. The subject devices have been investigated to UL 60320-1, cold condition. The device configuration and voltage rating are as indicated below:

Series	Electrical Rating	Configuration
4710	20A, 250 Vac	Sheet J
4710-5	20A, 250 Vac	Sheet J
4797	20A, 250 Vac	Sheet J and Sheet L
4797-5	20A, 250 Vac	Sheet J

USR - Indicates investigation to United States Standards UL 60320-1.

CNR - Indicates investigation to Canadian National Standards C22.2 No. CSA C22.2 No. 60320-1-11.

## ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Conditions of Acceptability - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

1. Series 4710 has been investigated for a current of 20 A with a maximum temperature rise of 24.2\_ degrees C.
2. The suitability of the mounting means shall be determined in the end use.

The snap panel mounting tabs have not been evaluated for mounting secureness.

3. The acceptability of the grounding connection shall be determined by the end product use engineer.

4. The IDC terminals have been evaluated to the requirements of UL 498, Heat Cycling & Vibration Test. These devices have been investigated for rated current (carried by each pole) with a maximum temperature rise as follows.

* Series	Current (A)	Wire type/size	Terminal Orientation	Temperature Rise
*4710	20	10)AWG Cu, Sol	Perpendicular	23
*4710	20	10)AWG Cu, Sol	Parallel	
*4710	20	12)AWG Cu, Sol	Perpendicular	24.2
*4710	20	12)AWG Cu, Sol	Parallel	

5. The placement of these devices within the equipment enclosure should be such that spacings between the live parts and the equipment are suitable for the particular application.

## NOMENCLATURE BREAKDOWN SERIES 4710

4710	-	0	X	X	X	-	0	0	0	0	-	X	XX	-	X	1	00
			I	II	III							IV	V		VI		

## I - Terminal L

- \* 1 = **IDC-Contact** 10 AWG
- \* 2 = **IDC-Contact** 12 AWG
- 4 = Solder Terminal
- 6 = Quick-connect 6.3 x 0.8 mm

## II - Terminal N

- \* 1 = **IDC-Contact** 10 AWG
- \* 2 = **IDC-Contact** 12 AWG

## III - Terminal PE

- \* 1 = **IDC-Contact** 10 AWG
- \* 2 = **IDC-Contact** 12 AWG

## IV - Arrangement

- 1 = along
- 2 = cross

## V - Panel mounting

- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.2 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm

## VI - Color

- 1 = black
- 2 = grey
- 3 = white

## NOMENCLATURE BREAKDOWN SERIES 4710-5

4710-5	X	X	X	-	X	X	X	X	-	X	XX	-	X	X	00
	I	II	III		IV	V	VI	VII		VIII	IX		X	XI	

## I - Terminal L

- \* 1 = **IDC-Contact** 10 AWG
- \* 2 = **IDC-Contact** 12 AWG
- 4 = Solder Terminal
- 6 = Quick-connect 6.3 x 0.8 mm
- 7 = PCB terminal 2.8 x 0.8 mm

## II - Terminal N

- \* 1 = **IDC-Contact** 10 AWG
- \* 2 = **IDC-Contact** 12 AWG

## III - Terminal PE

- \* 1 = **IDC-Contact** 10 AWG
- \* 2 = **IDC-Contact** 12 AWG

## IV - Light pipe position A

- 0 = without hole for light pipe
- 1 = with hole for light pipe

## V - Light pipe position B

Same numbers as "IV - Light pipe position A"

## VI - Light pipe position C

Same numbers as "IV - Light pipe position A"

## VII - Light pipe position D

Same numbers as "IV - Light pipe position A"

## VIII - Arrangement

- 1 = along
- 2 = cross

## IX - Panel mounting

- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.5 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm

## X - Color

- 1 = black
- 2 = grey
- 3 = white

## XI - Glow wire requirements (IEC)

- 0 = GWIT standard
- 1 = GWIT enhanced

## NOMENCLATURE BREAKDOWN SERIES 4797

4797	-	0	X	X	X	-	0	0	0	0	-	XX	-	X	<b>X</b>	-	00
			I	II	III							IV		V	<b>VI</b>		

## I - Terminal L

- 1 = Solder terminal
- 2 = Quick-connect 6.3 x 0.8 mm

## II - Terminal N

- 1 = Solder terminal
- 2 = Quick-connect 6.3 x 0.8 mm

## III - Terminal PE

- 0 = without terminal (PC II)
- 1 = Solder terminal
- 2 = Quick-connect 6.3 x 0.8 mm

## IV - Panel mounting

- 00 = screw mounting
- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.5 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm

## V - Color

- 1 = black
- 2 = grey
- 3 = white

## VI - Plastic

- 0 = **Fossil plastic**
- 1 = **Bio-plastic**

## NOMENCLATURE BREAKDOWN SERIES 4797-5

*4797- 5	X	X	X	-	X	X	X	X	-	<b>XX</b>	-	X	X	-	XX
	I	II	III		IV	V	VI	VII		VIII		IX	X		XI

## I - Terminal L

- 4 = PCB terminal, L = 34.0 mm
- 5 = PCB terminal, L = 30.6 mm

## II - Terminal N

- 4 = PCB terminal, L = 34.0 mm
- 5 = PCB terminal, L = 30.6 mm

## III - Terminal PE

- 4 = PCB terminal, L = 34.0 mm
- 5 = PCB terminal, L = 30.6 mm

## IV - Light pipe position A

- 0 = without hole for light pipe
- 1 = with hole for light pipe
- 3 = Light pipe, L = 27.5 mm
- 4 = Light pipe, L = 32.7 mm
- 5 = Light pipe, L = 37.4 mm
- 6 = Light pipe, L = 50.0 mm
- 7 = Light pipe, L = 28.5 mm

## V - Light pipe position B

Same numbers as "IV - Light pipe position A"

## VI - Light pipe position C

Same numbers as "IV - Light pipe position A"

## VII - Light pipe position D

Same numbers as "IV - Light pipe position A"

**\*VIII** - Panel mounting

- 10 = snap-in 1.0 mm
- 12 = snap-in 1.2 mm
- 15 = snap-in 1.5 mm
- 17 = snap-in 1.7 mm
- 20 = snap-in 2.0 mm
- 25 = snap-in 2.5 mm
- 30 = snap-in 3.0 mm

**IX** - Color

- 1 = black
- 2 = grey
- 3 = white

**X** - Plastic

- 0 = Fossil plastic

## XI - Customer specific type

- 00 = standard
- 01 = customer specific light pipe length